

Impel Plus Backplane Connectors and Cable Assemblies

molex

Impel Plus Backplane Connector System achieves data rates up to 56 Gbps with superior signal integrity performance and enables backward and forward compatibility with compact compliant pins

Features and Advantages


Compact, compliant-pin 56-Gbps backplane connector

Enables backward and forward compatibility with various high-end copper and cable architectures



Innovative signal beam interface

Improves insertion loss compared to in-line signal beams. Pushes interface resonance frequency past 30 GHz



Impel Plus 3-Pair, 2.35mm-Pitch Right-Angle Orthogonal Direct Connector System

Option for short compliant pin allowing 0.65mm backdrill and access to top layers for high-speed routing

Offers better signal integrity performance due to shallow PCB hole. Lowers PCB costs by reducing layers



Impel Plus 3-Pair, Right-Angle Daughtercard, 1.90mm Pitch


Small compliant pin (0.31mm ± -0.05)

Reduces crosstalk by enabling optimized routing or use of pinning via

Grounding tail aligner for lead frames and wafer shields
closer to daughtercard launch to improve ground return path
Minimizes impedance discontinuities. Reduces crosstalk

IEEE 10GBASE-KR and Optical Internetworking Forum (OIF) Stat Eye Compliant Channel
Demonstrates end-to-end channel performance compliance

92 Ohms nominal impedance
Minimizes impedance discontinuities in the channel



Impel Plus 4-Pair, Right-Angle Daughtercard, 1.90mm Pitch

3-, 4- and 6-pair daughtercards available with a range of column sizes
Delivers design flexibility

Molex patent-pending Impel Connector technology with tightly coupled differential-pair structure

Provides optimal signal integrity and mechanical isolation through the connector system

High-speed automation line is available for high-volume production of cable

Controlled manufacturing process provides cables with reliable and consistent signal integrity performance



Cable Assemblies Available with Impel Plus 3-, 4- and 6-Pair Daughtercards and Impel Cables (Assembly with Impel 6-Pair Daughtercard pictured)

Complete mechanical, electrical and testing capabilities available to deliver a complete backplane solution
Offers value-added cable trays

Assemblies with Impel Cables up to 3.0m long can be configured with 3-, 4- and 6-pair Impel Plus Daughtercards
Supports design flexibility to maximize density of differential pairs with cables

Impel Plus Backplane Connectors and Cable Assemblies



Applications

Telecommunications/Networking

- Servers
- Switches
- Routers

Data Center Solutions

- Servers
- Storage Systems

Medical

- Patient monitoring



High-End Server

Specifications

REFERENCE INFORMATION

Packaging: Tray
 UL File No.:
 Mates With: Impel Vertical Backplane Headers (see other available Impel header options)
 OD Daughtercard (Series 171510) mates with OD Header (Series 173460)
 Designed In: Millimeters
 RoHS: Yes
 Halogen Free: Yes

ELECTRICAL

Electrical
 Voltage (max.): 150V AC RMS
 Current (max): 0.75A
 Contact Resistance: 100mA; 20mV
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 500V

MECHANICAL

Insertion Force to PCB (max.): 26.69N per tail
 Mating Force: 60g per signal; 80g per shield
 Unmating Force (min.): 60g
 Durability (min.): 200 Cycles

PHYSICAL

Housing: LCP
 Contact: Copper Alloy
 Plating:
 Contact Area — 0.76 μm (30 μm) Gold (Au)
 Solder Tail Area — select Matte Tin (Sn)
 Underplating — Nickel (Ni)
 PCB Thickness (min.): 1.00mm
 Operating Temperature: -55° to +85°C

Ordering Information

Series No.	Component	Pitch (mm)	Number of Pairs
172730	Daughtercard	1.9	3
204066		1.9	4

Series No.	Component	Orientation	Pitch (mm)	Number of Pairs
171510	Orthogonal Direct Daughtercard	Right Angle	2.35	3
173460	Orthogonal Direct Header			

Series No.	Component	Pitch (mm)	Number of Pairs
Contact Molex	Daughtercard	3	4
		1.9	6

Custom Product	Description
Contact Molex	Assemblies with Impel Plus Daughtercard and Impel Cables

www.molex.com/link/impel.html

Molex is a registered trademark of Molex, LLC in the United States of America and may be registered in other countries; all other trademarks listed herein belong to their respective owners.