

# Power Products

Product Name	Current (Max) Per Pin	Version	PCB Termination	Pitch	Available Configurations	Wire Gauge (AWG)
<b>Micro-Fit 3.0</b> KK 254	4.0A	2 to 24	Single Row Through Hole	2.54mm (0.100")	W-to-B, B-to-B, 20 to 20	20 to 20
<b>Micro-Fit BMI</b> (Blind Mate Interface)	5.0A	4 to 24	Dual Row Through Hole and Compliant Pin	3.0mm (0.118")	W-to-W, W-to-B, B-to-B, 20 to 20	20 to 20
<b>MultiCat Mid-Power</b> KK 396	5.5A	8 and 20	Dual Row Through Hole	3.60mm (0.142")	W-to-W, W-to-B, 20 to 20	20 to 20
<b>Mini-Fit Jr.</b> KK 508	7.0A	2 to 12	Single Row Through Hole	3.96mm (0.156")	W-to-B, B-to-B, 18 to 18	18 to 18
<b>Mini-Fit BMI</b> (Blind Mate Interface)	7.0A	2 to 24	Single & Dual Row Through Hole	4.20mm (0.165")	W-to-W, W-to-B, 16 to 16	16 to 16
<b>Ultra-Fit</b>	13.0A	2 to 8 (Single Row), 4 to 16 (Dual Row)	Single & Dual Row Through Hole and Compliant Pin	4.20mm (0.165")	W-to-W, W-to-B, B-to-B, 16 to 16	16 to 16
<b>Sabre</b>	13.0A	2 to 8	Single Row Through Hole	5.70mm (0.224")	W-to-B, W-to-B, 14 to 14	14 to 14
<b>Mega-Fit</b>	23.0A	2 to 12	Single Row Through Hole	5.70mm (0.224")	W-to-B, 12 to 12	12 to 12
<b>Super Sabre</b>	34.0A	2 to 8	Single Row Through Hole	7.50mm (0.295")	W-to-W, W-to-B, 8 to 8	8 to 8
<b>MultiCat High-Power</b>	40.0A	3	Single Row & Circular Through Hole	7.40mm (0.291")	W-to-W, W-to-B, 8 to 8	8 to 8

Power Products  
05T\_021719  
Order No. 987650-9812  
© copyright 2019, Molex

Molex is a registered trademark of Molex, LLC in the United States of America and may be registered in other countries; all other trademarks listed herein belong to their respective owners.

**molex**